

## Preface

---

# ***Cellulose Fibre Insulation (CFI) For Buildings***

## Scope

These Evaluation Listings apply to treated, wood-based, cellulose fibre intended for use as thermal insulation (cellulose fibre insulation, CFI) in new and existing buildings. The continuous use temperature range is within  $-60^{\circ}\text{C}$  to  $90^{\circ}\text{C}$ . The proponent has demonstrated that the product meets at least one of the following standards:

- CAN/ULC-S703-01 (including Amendment 1), “Standard for Cellulose Fibre Insulation (CFI) for Buildings.”
- CAN/ULC-S703-09, “Standard for Cellulose Fibre Insulation (CFI) for Buildings.”

The standard describes two types of CFI. They are defined in CAN/ULC-S703-09 as follows:

- Type 1 is intended for pneumatic application into open areas with slopes up to 4.5:12, or injection application into closed cavities, such as walls, floors, and cathedral ceilings. Type 1 may also be manually applied (poured application).
- Type 2 is intended for spray application with water or liquid adhesive into open areas regardless of slope (eg. attics), exposed surfaces (eg. walls or ceilings) and/or into any open cavity (eg. wall, floor, or ceiling cavities) that may be closed later. This product may also contain internal binders to increase the adhesive/cohesive capabilities of the sprayed fibres in order to reduce settlement and/or ensure it remains in place.

## Standard (2001 and 2009 Versions)

**Table 1. Performance Requirements for Physical Properties of CFI (Type 1 and Type 2)**

Property	Unit	Requirement
Thermal resistivity	m·K/W	Minimum 18.5
Open flammability	W/cm <sup>2</sup>	Minimum 0.12
Open flammability permanency	W/cm <sup>2</sup>	Minimum 0.12
Surface burning characteristics <sup>(1)</sup>	FSI	Maximum 150 (Type 1) Maximum 25 (Type 2)
Smoulder resistance	%	Maximum 15
Moisture vapour sorption	%	Maximum 20
Corrosiveness	–	No perforations
Fungi resistance	–	Fungal growth shall not exceed that of the comparative item
Separation of chemicals	%	Maximum 1.5
Design density	kg/m <sup>3</sup>	As determined

**Table 2. Additional Requirements for Type 2 Product**

Property	Unit	Requirement
Added water <sup>(1)</sup>	%	Maximum 20
Design Moisture <sup>(2)</sup>	%	Maximum 20
Settlement – open spaces	%	Maximum 5
Cohesion/adhesion exposed surfaces <sup>(2)</sup>	–	Minimum 5 times the mass of the material under the test plate

### Notes to Tables 1 & 2:

- (1) Requirement in CAN/ULC-S703-01 version only.
- (2) Requirement in CAN/ULC-S703-09 version only.

## Labelling

The standard requires that each bag of insulation be identified with the following information:

- manufacturer’s name and address;
- trade name of the product;
- generic product name;
- material type and sub-type (i.e. Type 1 (open spaces) and/or Type 2 (closed cavities));
- package mass;
- standard number CAN/ULC-S703;
- day/month/year of manufacture or traceable code number;
- coverage table(s) providing the information described in the appropriate Subsection of the standard; and
- a cautionary note as follows:
  - “CAUTION: Maintain building, electrical, gas and oil safety code required clearances between the insulation and heat-emitting devices, such as fuel-burning appliances, chimney pipes, ducts and vents to these appliances (at least 50 mm) and recessed light fixtures (at least 75 mm) unless approved for insulation contact.”

## **National Building Code of Canada (NBC)**

### *NBC References*

The CAN/ULC-S703-01 standard is referenced in Clause 9.25.2.2. (1)(e) and Table 5.10.1.1. of Division B of the NBC 2010,

The CAN/ULC-S703-09 standard is not referenced in the NBC 2010.



# Evaluation Listing

## CCMC 09217-L

MASTERFORMAT: 07 21 23.01  
 Issued: 1981-10-20  
 Re-evaluated: 2011-04-24  
 Revised: 2011-08-11  
 Re-evaluation due: 2014-06-01

# *Climatizer Plus/Weathershield™/Homecare/Mister Insulation*

## 1. Evaluation

The product conforms to CAN/ULC-S703-01, Type 1. The thermal resistance value is  $26.15 \text{ m}^2 \cdot \text{KW}^{-1} / \text{m}$  at the design density of  $25.63 \text{ kg/m}^3$ . This product shall be installed as outlined in the Preface and as per the following application chart.

RSI Value ( $\text{m}^2 \cdot \text{K/W}$ )	Minimum Applied Thickness (mm)	Minimum Settled Thickness (mm)	Mass Per Unit Area ( $\text{kg/m}^2$ )	Coverage per 15.0-kg Bag ( $\text{m}^2$ )
1.7	74	66	1.71	8.82
2.1	91	81	2.08	7.21
2.6	112	100	2.57	5.82
3.5	136	121	3.10	4.80
4.4	170	152	3.90	3.80
5.3	230	205	5.25	2.85
5.6	242	216	5.55	2.70
7.0	302	270	6.94	2.16
8.8	381	340	8.72	1.72

## 2. Description

A cellulose-fibre, thermal building insulation made from clean paper and treated with chemicals. The paper is at least 95% used or unused, or a combination of both, newsprint feedstock with a maximum 5% of paper obtained from telephone directories, paperback books and glossy paper. Glossy paper does not exceed 1%.

### 3. Standard and Regulatory Information

See the [Preface](#) and the standard for explanation.

Listing Holder: Climatizer Insulation Inc.  
120 Claireville Drive  
Etobicoke, ON M9W 5Y3  
Tel: 416-798-1235  
Fax: 416-798-1311  
E-mail: [info@climatizerinsulation.com](mailto:info@climatizerinsulation.com)  
Web: [www.climatizerinsulation.com](http://www.climatizerinsulation.com)

Plant(s): Etobicoke, ON

*This Listing is issued by the Canadian Construction Materials Centre, a program of the Institute for Research in Construction at the National Research Council of Canada. The Listing must be read in the context of the entire CCMC Registry of Product Evaluations.*

*Readers must confirm that the Listing is current and has not been withdrawn or superseded by a later issue. Please refer to <http://www.nrc-cnrc.gc.ca/eng/services/irc/ccmc.html>, or contact the Canadian Construction Materials Centre, Institute for Research in Construction, National Research Council of Canada, 1200 Montreal Road, Ottawa, Ontario, K1A 0R6. Telephone (613) 993-6189. Fax (613) 952-0268.*

***NRC has evaluated the material, product, system or service described herein only for those characteristics stated herein. The information and opinions in this Listing are directed to those who have the appropriate degree of experience to use and apply its contents. This Listing is provided without representation, warranty, or guarantee of any kind, expressed, or implied, and the National Research Council of Canada (NRC) provides no endorsement for any evaluated material, product, system or service described herein. NRC accepts no responsibility whatsoever arising in any way from any and all use and reliance on the information contained in this Listing. NRC is not undertaking to render professional or other services on behalf of any person or entity nor to perform any duty owed by any person or entity to another person or entity.***